

50 Amp Terrapin Station II™ to Straight Blade and Locking Receptacles, Feed Thru for Construction Site Use

LEX
We Deliver the Power™

PowerHOUSE™
Portable Distribution Boxes

UL US LISTED
TYPE 3R



Catalog Number:
T2-A2-6A1E

Description:

50 Amp, Single Phase, 3 Pole, 4 Wire, 125/250 VAC, Terrapin Station II™ Enclosure, California-style locking inlet to (6) NEMA 5-20, 20 Amp, 125 VAC GFCI protected duplex receptacles and (1) NEMA L6-30, 30 Amp, 250 VAC locking receptacle, NEMA TYPE 3R Rainproof

Typical Application:

The PowerHOUSE™ Terrapin Station II™ power distribution box meets stringent UL, NEC and OSHA requirements for indoor or outdoor construction site applications where open-neutral ground fault protection and weather resistance is needed. The box delivers power from electrical panels or portable generators and is ideal for power tools, portable lights, chargers and other equipment.

Markets Served:

Construction, Electrical Distribution, Maintenance, Shipbuilding, Generator Rental and Entertainment

LEX
We Deliver the Power™

Lex Products Corporation
15 Progress Drive
Shelton CT 06484
203.363.3738
203.363.3742 Fax

Lex West
11847 Sheldon Street
Sun Valley, CA 91352
818.768.4474
818.768.4040 Fax

www.lexproducts.com
info@lexproducts.com
800.643.4460

© Copyright Lex Products 2014

Produced in the United States of America
All Rights Reserved.

Lex Products logo and lexproducts.com are trademarks or registered trademarks of Lex Products in the United States, other countries, or both.

Features & Benefits:

- Meets UL, NEC and OSHA requirements for construction site use
- Meets OSHA Regulation 20, Part 1926, Subpart K standards for open-neutral GFCI protection for enhanced safety
- Heavy duty molded rubber enclosure is fully insulated and resistant to shock, impact and corrosion for years of trouble-free service versus painted metal
- Thermal magnetic circuit breakers are located under a heavy duty rubber, waterproof, self-closing lid for enhanced breaker protection
- Weather resistant GFCI protection helps to prevent unsafe operating conditions and nuisance tripping
- GFCI module possesses LED beacon to indicate device status
- Straight blade model features duplex receptacles, providing 2x more outlets than single version boxes
- cULus Listed and TYPE 3R Rainproof for outdoor use
- Feed thru feature allows multiple boxes to be placed along one feed
- Spring-loaded covers protect receptacles and inlets from dirt and moisture intrusion
- Lightweight and compact for easy portability and storage
- Heavy-duty aluminum legs position the box at the NEC regulatory height of 6 inches while allowing for storage and transport stacking
- Molded handle enhances portability while improving stackability of multiple units

Specifications:

Rating	50 Amp, Single Phase (H, H, N, G), 3 Pole, 4 Wire, 125/250 VAC
Environmental Rating	NEMA TYPE 3R Rainproof
Input	(1) 50 Amp, Single Phase, 3 Pole, 4 Wire, 125/250 VAC, California-style locking inlet
Output	(6) GFCI protected, NEMA 5-20, 20 Amp, Single Phase, 2 Pole, 3 Wire, 125 VAC duplex receptacles; (1) NEMA L6-30, 30 Amp, Single Phase, 2 Pole, 3 Wire, 250 VAC locking receptacle
Feed Thru	(1) 50 Amp, Single Phase, 3 Pole, 4 Wire, 125/250 VAC, California-style locking receptacle
Overcurrent Protection	(6) 20 Amp, Single Pole branch-rated circuit breakers, (1) 30 Amp, Double Pole branch-rated circuit breaker
Dimensions	14.25" L x 14.25" W x 17.5" H
Weight	29.0 lbs